

PICO Electronics社 力率改善(PFC) AC-DCコンバータ ・ 3相入力

型名	入力	出力電圧(V)	出力電力(W)	外形寸法 W x D x H mm
AC3-5S	3相 166-250VAC 360-800Hz	5	150	64 x 117 x 21
AC3-9S	3相 166-250VAC 360-800Hz	9	250	64 x 117 x 21
AC3-12S	3相 166-250VAC 360-800Hz	12	300	64 x 117 x 21
AC3-15S	3相 166-250VAC 360-800Hz	15	300	64 x 117 x 21
AC3-24S	3相 166-250VAC 360-800Hz	24	300	64 x 117 x 21
AC3-28S	3相 166-250VAC 360-800Hz	28	300	64 x 117 x 21
AC3-48S	3相 166-250VAC 360-800Hz	48	300	64 x 117 x 21
AC3-100S	3相 166-250VAC 360-800Hz	100	250	64 x 117 x 21
AC3-125S	3相 166-250VAC 360-800Hz	125	250	64 x 117 x 21
AC3-150S	3相 166-250VAC 360-800Hz	150	250	64 x 117 x 21
AC3-175S	3相 166-250VAC 360-800Hz	175	250	64 x 117 x 21
AC3-200S	3相 166-250VAC 360-800Hz	200	250	64 x 117 x 21
AC3-225S	3相 166-250VAC 360-800Hz	225	250	64 x 117 x 21
AC3-250S	3相 166-250VAC 360-800Hz	250	250	64 x 117 x 21
AC3-275S	3相 166-250VAC 360-800Hz	275	250	64 x 117 x 21
AC3-300S	3相 166-250VAC 360-800Hz	300	250	64 x 117 x 21
HPHA1	3相 166-250VAC 47-440Hz	365	1000	64 x 117 x 13
HPHA2	3相 166-250VAC 47-440Hz	365	2000	64 x 117 x 13

備考：EN/IEC 61000-3-2（電源電圧の高調波電流の規格）にミート